

041 decotric Ready-mixed paste - special decotric Fertigkleister - Spezial

Ready-mixed wallpapering machine paste with synthetic resin

Corresponds to the approach proportions recommended by wallpaper manufacturers 1:20

Instructions for use:

decotric Ready-mixed paste - special is ideally suited for reliable, secure pasting of vinyl wallpapers, structured vinyl wallpapers, woodchip wallpapers, heavyweight paper wallpapers, embossed wallpapers, textile wallpapers and similar wall coverings.

Ideally suited for use with standard commercial wallpapering machines.

Technical specifications:

Components:	Cellulose ether, synthetic resin dispersion, additives
Density:	1.0 g/cm ³
pH-value:	8-9
Usage:	approx. 200-250 g/m ²
Frost-resistance:	to -20 °C

Surface preparation:

The surface must be dry, firm and free of dust and grease. Remove old, peeling wallpapers and distemper paints using *decotric Wallpaper Remover*. Make good cracks and holes using *decofill Interior* or *decomur Super Bonding Filler*. Prime highly absorbent, sanding and chalking surfaces with *decotric Deeply Penetrating Primer – Solvent Free*.

Water-soluble contaminations in the surface, which could show through when wallpapered over, should be isolated using *decotric Insulating Spray*. To make a subsequent change of wallpaper easier, we recommend priming the surface with *decotric Wallpaper Base Primer 'Tapeten-Wechselgrund'*, especially when hanging washable wallpapers.

Application:

Apply the adhesive to the wallpaper using a wallpapering machine or brush, fold the fold the pasted ends inwards and hang after an adequate soaking time. Always observe the wallpapering machine and wallpaper manufacturer's instructions for use.

Do not use if the object and/or room temperature are below + 5° Celsius!
Clean tools in water after use.

Storage:

Store in a cool and dry place.
Store container well sealed!
If the product freezes, it is nevertheless usable after thawing.

Article no.:

041

Available size:

16 kg