




Specification according EN 548 / EN ISO 24011

Marmorette LPX 2.5 mm

Marmorette LPX 3.2 mm

	EN 548 / EN ISO 24011	Linoleum with LPX Finish	Linoleum with LPX Finish	
Structure	Type of flooring	EN 548 / EN ISO 24011	Linoleum with LPX Finish	
	Pattern		marbled	
	Overall thickness	EN 428 / EN ISO 24346	2.5 mm	3.2 mm
	Backing		Jute fabric	Jute fabric
	Classification	EN 685 / EN ISO 10874	Class 23 / 34 / 42/43*	Class 23 / 34 / 42/43*
	Sheet width	EN 426 / EN ISO 24341	200 cm	200 cm
	Sheet length	EN 426 / EN ISO 24341	20 - 31 m	20 - 31 m
	Total weight	EN 430 / EN ISO 23997	2900 g/m ²	3800 g/m ²
Safety Criteria	Flammability	EN 13501-1	C _{fl} - s1, adhered according to certificate, see www.dlw.eu	C _{fl} - s1, adhered according to certificate, see www.dlw.eu
	Slip resistance	ASR A1.5 / BGR 181	R9	R9
	Dynamic coefficient of friction	EN 13893	DS (> 0.30)	DS (> 0.30)
	REACH Regulation No. 1907/2006	Article 33	contains no substances mentioned in the SVHC-list	
Performance	Impact sound reduction	EN ISO 10140	5 dB	6 dB
	Residual indentation	EN 433 / EN ISO 24343	≤ 0.15 mm	≤ 0.15 mm
	Colour fastness	ISO 105-B02	≥ rating 6	≥ rating 6
	Vertical resistance R _v	EN 1081	-	-
	Electrical insulation to ground	VDE 0100	> 200 kOhm	> 200 kOhm
	Static electrical charge	EN 1815	app. 2.0 kV	app. 2.0 kV
	Thermal resistance	EN 12667	0.015 m ² K / W	0.018 m ² K / W
	Thermal conductivity	EN 12524	0.17 W / m K	0.17 W / m K
	Resistance against chemicals	EN 423 / EN ISO 26987	 resistance to fat and mineral oil and short-term resistance against diluted acids	resistance to fat and mineral oil and short-term resistance against diluted acids
	Castor chair	EN 425	 suitable (Type W)	suitable (Type W)
	Flexibility	EN 435 / EN ISO 24344	∅ 40 mm	∅ 50 mm
	Warmwater-underfloor heating		 suitable (max. 29°C)	
Antibacterial activity	JIS Z 2801	DLW Linoleum has an antibacterial activity		

*Any requirements for class 43 should be determined and agreed between the parties concerned, taking into account specification of use.



EN 14041: 2004
05
1658-DOP-101

Manufactured by:
DLW Flooring GmbH
Ludwig-Kaufmann-Str. 13
D-27753 Delmenhorst



DLW flooring products are to be installed in full accordance with DLW Flooring installation instructions and recognised trade standards. An effective, regular cleaning and maintenance programme is vital for retaining a high appearance level. DLW flooring products should only be used as floorcoverings. Note: DLW Flooring reserve the right to amend this specification without giving prior notice. For the latest versions of the technical specifications, check our internet site: www.dlw.eu