

QUALITY
ORDER CODE

DATE: **30/11/2018**
REPLACES: 12/10/2017

WIDTH (±) cm
TYPE
GAUGE AND TYPE
TEXTURING
DYEING/PRINT METHOD

PILE COMPOSITION
FIBRE BRAND
WOOLMARK
MOTHPROOF

PRIMARY BACKING

SECONDARY BACKING

PILE WEIGHT (±) gr/m²
TOTAL WEIGHT (±) gr/m²

EFFECTIVE PILE HEIGHT (±) mm
TOTAL HEIGHT (±) mm
NUMBER OF KNOTS (±) m²
STITCHES OVER WIDTH (±) / 10 cm
STITCHES OVER LENGTH (±) / 10 cm

REPEAT TUFTING DESIGN L/W (±) mm
REPEAT PRINTING DESIGN L/W (±) mm

ROLL LENGTH (±) m
PILE IN/OUT

LANO CLASSIFICATION

BEDROOM
LIVING ROOM
OFFICE
CASTOR ROLLCHAIRS DOMESTIC USE
CASTOR ROLLCHAIRS PROFESSIONAL USE
STAIRS DOMESTIC USE
STAIRS PROFESSIONAL USE
ELECTROSTATIC BEHAVIOUR
UNDERFLOOR HEATING
BATH ROOM
NON-FRAY
PERSONAL COMPUTER

PRODIS-NUMBER

GUT-NUMBER
DIBT

UPEC n°
CLASSIFICATION

HQE
EN 1307

ADDITIONAL CHARACTERISTICS EN 1307

LUXURY CLASS

FIRE RESISTANCE EUROPE

FIRE RESISTANCE UK

LANO CLASSIFICATION
CLASSIFICATION BS7131

EN 13501-1

BS 4790

FLAIR CONCRETE SB
FLC

± 400
COLLECTION
1/10" CUT LOOP

PIECE DYED

PA 6.6

NON WOVEN

WOVEN SYNTHETIC SECONDARY BACKING

± 1.000
± 2.250

± 6,0
± 8,5
± 236.400
± 39,40
± 60,00

± 2370,00 / 3900,00
±

± 30
PILE IN

✓
✓
✓
✓
✓
✓
✓
ANTISTATIC
✓

1FEBA2ED

17/314-01
U3P3E1C0

Cl. 33
Commercial Heavy



LC3



Bfl-s1



LOW RADIUS

QUALITY

IMPACT SOUND INSULATION

(±) dB

ISO 140/8

± 25



THERMAL RETENTION

(±) m²/KW

ISO 8302

± 0,075



TOG rating

(±)

± 0,75

PERMANENTLY ANTISTATIC

(±) volt

ISO 6356

≤ 2000



LIGHTFASTNESS

ISO 105-B02

≥ 5

RUBBINGFASTNESS DRY

ISO 105 X12

≥ 3-4

RUBBINGFASTNESS WET

ISO 105 X12

≥ 3

WATERFASTNESS CHANGE IN COLOUR

ISO 105-E01


≥ 3-4

WATERFASTNESS STAINING

ISO 105-E01

≥ 2-3

LABEL CE



RECOMMENDED INSTALLATION

ALL-OVER STICK DOWN
WITH EC1 APPROVED ADHESIVE

MANUFACTURING TOLERANCE

(±) These details are approximate. Due to method of manufacture perfect pattern and/or colour matching cannot be guaranteed. In cut-pile carpeting, in rare cases, shading/pile reversal may occur without affecting its fitness for use. Shading/pile reversal can not be considered as a manufacturing or a material defect and will not affect the durability of the carpet.

AVAILABLE
FROM

COLOURS

SB 400

FLC

0183 RUM 3
0703 NAVY 3
0813 CHARCOAL 3
0843 MOONSHINE 3
0853 MOONBEAM 3
0863 GRANITE 3
0893 SNOW 3

AVAILABLE
FROM

SB 400

FLC



WE RESERVE THE RIGHT TO
ALTER TECHNICAL SPECIFICATIONS
WITHOUT PRIOR NOTICE

(7)