

QUALITY
ORDER CODE

DATE: **30/11/2018**
REPLACES: 12/10/2017

WIDTH (±) cm
TYPE
GAUGE AND TYPE
TEXTURING
DYEING/PRINT METHOD

PILE COMPOSITION
FIBRE BRAND
WOOLMARK
MOTHPROOF

PRIMARY BACKING

SECONDARY BACKING

PILE WEIGHT (±) gr/m²
TOTAL WEIGHT (±) gr/m²

EFFECTIVE PILE HEIGHT (±) mm
TOTAL HEIGHT (±) mm
NUMBER OF KNOTS (±) m²
STITCHES OVER WIDTH (±) / 10 cm
STITCHES OVER LENGTH (±) / 10 cm

REPEAT TUFTING DESIGN L/W (±) mm
REPEAT PRINTING DESIGN L/W (±) mm

ROLL LENGTH (±) m
PILE IN/OUT

LANO CLASSIFICATION

BEDROOM
LIVING ROOM
OFFICE
CASTOR ROLLCHAIRS DOMESTIC USE
CASTOR ROLLCHAIRS PROFESSIONAL USE
STAIRS DOMESTIC USE
STAIRS PROFESSIONAL USE
ELECTROSTATIC BEHAVIOUR
UNDERFLOOR HEATING
BATH ROOM
NON-FRAY
PERSONAL COMPUTER

PRODIS-NUMBER

GUT-NUMBER
DIBT

UPEC n°
CLASSIFICATION

HQE
EN 1307

ADDITIONAL CHARACTERISTICS EN 1307

LUXURY CLASS

FIRE RESISTANCE EUROPE

FIRE RESISTANCE UK

LANO CLASSIFICATION
CLASSIFICATION BS7131

EN 13501-1

BS 4790

FLAIR DUNE SB
FLR

± 400
COLLECTION
1/10" CUT LOOP

PIECE DYED

PA 6.6

NON WOVEN

WOVEN SYNTHETIC SECONDARY BACKING

± 1.000
± 2.250

± 6,0
± 8,5
± 236.400
± 39,40
± 60,00

± 760,00 / 970,00
±

± 30
PILE IN

✓
✓
✓
✓
✓
✓
✓
ANTISTATIC
✓

DEDB9DB6

17/314
U3P3E1C0

Cl. 33
Commercial Heavy



LC3



Bfl-s1



LOW RADIUS

QUALITY

IMPACT SOUND INSULATION

(±) dB

ISO 140/8

± 25



THERMAL RETENTION

(±) m²/KW

ISO 8302

± 0,075



TOG rating

(±)

± 0,75

PERMANENTLY ANTISTATIC

(±) volt

ISO 6356

≤ 2000



LIGHTFASTNESS

RUBBINGFASTNESS DRY

RUBBINGFASTNESS WET

WATERFASTNESS CHANGE IN COLOUR

WATERFASTNESS STAINING

ISO 105-B02

ISO 105 X12

ISO 105 X12

ISO 105-E01

ISO 105-E01

≥ 5

≥ 3-4

≥ 3

≥ 3-4

≥ 2-3

LABEL CE

RECOMMENDED INSTALLATION

MANUFACTURING TOLERANCE

(±) These details are approximate. Due to method of manufacture perfect pattern and/or colour matching cannot be guaranteed. In cut-pile carpeting, in rare cases, shading/pile reversal may occur without affecting its fitness for use. Shading/pile reversal can not be considered as a manufacturing or a material defect and will not affect the durability of the carpet.

AVAILABLE
FROM

AVAILABLE
FROM

COLOURS



SB 400

FLR

083 PURPLE 3
103 RUBY 3
173 SALMON 3
183 RUM 3
302 MAHOGANY 2
703 NAVY 3
733 AZURE 3
792 MIDNIGHT 2
813 CHARCOAL 3
843 MOONSHINE 3
853 MOONBEAM 3
863 GRANITE 3
882 PEARL 2
893 SNOW 3

SB 400

FLR

WE RESERVE THE RIGHT TO
ALTER TECHNICAL SPECIFICATIONS
WITHOUT PRIOR NOTICE

(14)

FLAIR DUNE SB



EN 14041
DOP 1038-125029
NB 2401



LANO NV - Venetielaan 33
B-8530 HARELBEKE
Floor carpets to use in
buildings

ALL-OVER STICK DOWN
WITH EC1 APPROVED ADHESIVE