



# MIPOLAM CLASSIC

[gerflor.com](http://gerflor.com)



**Gerflor®**  
theflooringgroup

# MIPOLAM CLASSIC



2 m



608 x 608 mm



Abrasion group  
2 mm



Medium to heavy traffic



PUR  
TREATED



**0125 Truffle**  
NCS: 6005-Y50R / LRV: 17.5



**0124 Tortora**  
NCS: 3010-Y20R / LRV: 36.9



**0014 Brown**  
NCS: 3010-Y40R / LRV: 39.2



**0301 Beige**  
NCS: 1505-Y30R / NCS: 65.5



**0003 Ivory**  
NCS: 2010-Y30R / LRV: 56.1



**0006 Honey**  
NCS: 2020-Y30R / LRV: 46.0



All colours available as 300 x 300mm tiles upon request for a minimum order quantity of 500 sqm - ▲ Thickness: 1.5 mm - Sheet format only



**0123 Corallo**  
NCS: 2060-Y80R / LRV: 21.2



**0013 Pewter**  
NCS: 6502-B / LRV: 18.2



**0005 Steel**  
NCS: 3502-B / LRV: 38.3



**0108 Pepper**  
NCS: 2500-N / LRV: 49.1



**0303 Grey**  
NCS: 3005-B20G / LRV: 42.2



**0002 Platinum**  
NCS: 2002-B / LRV: 56.1





**0127 Bermuda**  
NCS: 5030-B10G / LRV: 13.4



**0126 Nordica**  
NCS: 2040-B / LRV: 34.2



**0010 Azure**  
NCS: 3030-B / LRV: 32.6



**0120 Borneo**  
NCS: 4020-G40Y / LRV: 27.5



**0122 Pineapple**  
NCS: 1050-Y20R / LRV: 51.8



**0121 Green Leaf**  
NCS: 2040-G60Y / LRV: 41.1



# MIPOLAM CLASSIC

### Performances and benefits



Homogeneous vinyl flooring suitable for medium to heavy duty traffic areas



Directional design available in 18 references



2 mm thickness



Flexible, easy to install and to weld

### Maintenance



Ease of maintenance, no immediate use of an acrylic emulsion after installation

### Don't forget our complementary ranges!



Handrails



Wall Coverings & Protections



Entrance mats



Skirtings & Profiles

## EASIER MAINTENANCE - LOWER ENVIRONMENTAL IMPACT



### 100 % RECYCLABLE

- 100 % recyclable product



### RECYCLED CONTENT

- 25 % recycled content
- 100 % REACH compliant recycled content



### INDOOR AIR QUALITY

- TVOC emissions 100 times below standards (TVOC < 10 µg/m³ after 28 days)
- Comply with AgBB protocol
- No formaldehyde emission



### LCA

- Eco-designed according to a product specific Life Cycle Analysis
- Product specific EPD (Environmental Products Declaration) available
- Manufactured in an Iso 14001 certified site
- Contribution to many Green Building Schemes (LEED, HQE, BREEAM...)



### COMPOSITION

**100% REACH compliant**

- FREE of formaldehyde
- FREE of heavy metals
- FREE of solvent



### WELLNESS

**Health**

- Walking Comfort: B Class

|                                  |                         |         | MIPOLAM CLASSIC<br>1.5 mm                                                            | MIPOLAM CLASSIC<br>2 mm                                                               |
|----------------------------------|-------------------------|---------|--------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
| DESCRIPTION                      |                         |         |                                                                                      |                                                                                       |
| Total Thickness                  | EN ISO 24346 (EN 428)   | mm      | 2.0                                                                                  | 2.0                                                                                   |
| Weight                           | EN ISO 23997 (EN 430)   | g/sq.m  | 2520                                                                                 | 3300                                                                                  |
| Width/Length of Sheet            | EN ISO 24341 (EN 426)   | cm/lm   | 200/20                                                                               | 200/20                                                                                |
| Tile size                        | EN ISO 24342 (EN 427)   | mm      | -                                                                                    | 300 x 300* / 608 x 608                                                                |
| Number of tiles per package      | -                       | -       | -                                                                                    | 50 / 20                                                                               |
| CLASSIFICATION                   |                         |         |                                                                                      |                                                                                       |
| Norm/Product Specification       | -                       | -       | EN ISO 10581 (EN 649)                                                                | EN ISO 10581 (EN 649)                                                                 |
| European classification          | EN ISO 10874 (EN 685)   | class   | 23-31                                                                                | 34-43                                                                                 |
| Fire Rating                      | EN 13 501-1             | class   | Bfl-s1                                                                               | Bfl-s1                                                                                |
| Static electrical propensity     | EN 1815                 | kV      | < 2                                                                                  | < 2                                                                                   |
| PERFORMANCE                      |                         |         |                                                                                      |                                                                                       |
| Wear resistance                  | EN 660.2                | mm³     | ≤ 15                                                                                 | ≤ 7.5                                                                                 |
| Wear Group                       | NF 189                  | group   | F                                                                                    | M                                                                                     |
| Type Binder content              | EN ISO 10581            | type    | II                                                                                   | II                                                                                    |
| Dimensional stability            | EN ISO 23999 (EN 434)   | %       | ≤ 0.40                                                                               | sheet ≤ 0.40<br>tile ≤ 0.25                                                           |
| Residual indentation             | EN ISO 24343-1 (EN 433) | mm      | ≈ 0.03                                                                               | ≈ 0.03                                                                                |
| Castor Chair test (type W)       | ISO 4918 (EN 425)       | -       | OK                                                                                   | OK                                                                                    |
| Thermal Conductivity             | EN ISO 10456 (EN 12524) | W/(m.K) | 0.25                                                                                 | 0.25                                                                                  |
| Colour Fastness                  | EN 20 105-B02           | degree  | ≥ 6                                                                                  | ≥ 6                                                                                   |
| Surface Treatment                | -                       | -       | PUR                                                                                  | PUR                                                                                   |
| Chemical Products fastness       | EN ISO 26987 (EN 423)   | class   | OK                                                                                   | OK                                                                                    |
| ENVIRONMENT / INDOOR AIR QUALITY |                         |         |                                                                                      |                                                                                       |
| TVOC after 28 days               | ISO 16000-6             | µg/ m³  | < 10                                                                                 | < 10                                                                                  |
| CE MARKING                       |                         |         |                                                                                      |                                                                                       |
| CE                               | EN 14 041               | -       |  |  |
|                                  |                         |         |   |  |

\* upon special request

Product description & technical data sheet in *Dutch / French, Spanish / Portuguese, Italian, Swedish, Norwegian* on Gerflor websites.

INSTALLATION

Laying is the responsibility of the installer. Installation should be made in accordance with installation guidelines supplied and regularly updated by Gerflor’s Technical Department. Installation should be carried out in accordance with local standards. Subfloor to be smooth, hard, clean and dry prior to laying. Where applicable the subfloor must incorporate an effective Damp Proof Membrane. The material must be allowed to acclimatise 24 hours prior to installation in a room temperature of between 18-24°C. All seams must be heat welded using Gerflor matching weld rod.

MAINTENANCE

Maintenance should be carried out regularly to retain the appearance and durability of the floor. The floor covering should be maintained with regular sweeping and damp mopping using a neutral cleaner, or auto scrubber machine with an appropriate pad.  
 Rubber leaves indelible stains on vinyl floorings: do not use mats with rubber backing and replace tubular furniture feet with those made of PVC or polyamide. Place mats of sufficient length at entrances to reduce outside sources of dirt.  
Further installation and maintenance instructions are available from Gerflor.

MIPOLAM CLASSIC, LESS SPEAKING FOR MORE ACTIONS



**COMPOSITION**  
100% REACH compliant



**INDOOR AIR QUALITY**  
100 times below standards  
(TVOC < 10 ug/m³ after 28 days)



**RECYCLED CONTENT**  
25 %



**RECYCLABILITY**  
100 %



**LCA**  
Eco-designed according to a product specific life cycle analysis



**WELLNESS**  
Walking comfort: B class