

Wiltax

Medaillon 2505

30

40

10



Midnight 30



▲ Regal Red 10



▲ Midnight 30



▲ Meadow 40

| | | | |
|-----------------------|-----------------------------------|--------------------|---|
| Manufacturing process | Woven face-to-face Wilton | Number of points | ca. 482.800m² |
| Pile content | 100% PP StainSafe® | Width | 400 cm |
| Pile weight | ca. 2.100 gr/m² | Design Repeat | 100 (W) x 100 (H) cm |
| Total weight | ca. 2.576 gr/m² | Light Fastness | 5-6 |
| Pile height | ca. 10 mm | Water resistance | 4-5 |
| Total height | ca. 13 mm | Characteristics | Heavy Domestic / Medium contract use |
| Shot density | 71/10 cm | Thermal resistance | 0,15 m² K/W (Tog 1,5) |
| Warp rate | 34/10 cm | Installation | Underlay and gripper rods BS5325 |

EN14041

11

Balta Industries - Wakkensteenweg 2
BE - 8710 Sint-Baafs-Vijve

DOP: 1010#BC0AEL

Textile Floor Covering EN1307

www.baltamediabank.com

1152D234

www.pro-dis.info

www.stain-safe.com

08/2017

Onder voorbehoud van de wijzigingen van de technische specificaties - Kijk voor de uitgebreide garantievoorwaarden op www.stain-safe.com
 Sous réserve de modifications techniques - Pour le détail des conditions de garantie, rendez-vous sur www.stain-safe.com
 Unter Vorbehalt von Änderungen der technischen Daten - Detaillierte Garantiebedingungen finden Sie auf www.stain-safe.com
 All rights reserved to alter technical specifications - For detailed warranty conditions, see www.stain-safe.com

Wakkensteenweg 2, 8710 Sint-Baafs-Vijve, Belgium
 T +32 (0)56 62 22 11, info@baltagroup.com, www.baltagroup.com

Wiltax new

2561 Arlington • 10

10



Arlington Court Rouge 10



▲ 10

| | | | |
|-----------------------|-----------------------------------|--------------------|---|
| Manufacturing process | Woven face-to-face Wilton | Number of points | ca. 482.800m² |
| Pile content | 100% PP StainSafe® | Width | 400 cm |
| Pile weight | ca. 2.100 gr/m² | Design Repeat | 100 (W) x 105 (H) cm |
| Total weight | ca. 2.570 gr/m² | Light Fastness | 5-6 |
| Pile height | ca. 10 mm | Water resistance | 4-5 |
| Total height | ca. 13 mm | Characteristics | Heavy Domestic / Medium contract use |
| Shot density | 71/10 cm | Thermal resistance | 0,15 m² K/W (Tog 1,5) |
| Warp rate | 34/10 cm | Installation | Underlay and gripper rods BS5325 |

EN14041

11

Balta Industries - Wakkensteenweg 2
BE - 8710 Sint-Baafs-Vijve

DOP: 1010#B00AEL

Textile Floor Covering EN1307

www.baltamediabank.com

1152D234

www.pro-dis.info



Onder voorbehoud van de wijzigingen van de technische specificaties - Kijk voor de uitgebreide garantievoorwaarden op www.stain-safe.com
 Sous réserve de modifications techniques - Pour le détail des conditions de garantie, rendez-vous sur www.stain-safe.com
 Unter Vorbehalt von Änderungen der technischen Daten - Detaillierte Garantiebedingungen finden Sie auf www.stain-safe.com
 All rights reserved to alter technical specifications - For detailed warranty conditions, see www.stain-safe.com



Wakkensteenweg 2, 8710 Sint-Baafs-Vijve, Belgium
 T +32 (0)56 62 22 11, info@baltagroup.com, www.baltagroup.com

