

Dimensions everroll® rolls	Roll width: 1,250 mm Thickness: 4 and 6 mm = Roll length: 20.000 mm Thickness: 8 - 12 mm = Roll length: 10.000 mm
Dimensions everroll® puzzletile	Outer dimensions: approx. 600 x 600 mm Net coverage: approx. 570 x 570 mm One Plate = approx. 0,325 m² More Information about everroll® puzzletile
Material	Synthetic EPDM rubber, Polyurethane
Reaction to fire	Cfl-s1 difficult to ignite
Thermal Conductivity	0,12 W/mK, suitable for underfloor heating
Impact Sound Insulation	Improvements of impact sound can be attained according to everroll® thickness and everroll® system composition. The degree of impact sound improvement for a 6-mm-thick everroll® flooring is 15 dB in accordance with DIN ISO 140-8.

everroll® xtreme is particularly well suited to the following areas:

Areas Exposed to Strong Sunlight or Artificial Light

everroll® xtreme has a light-fastness rating of 7 "excellent". No discolouration beneath the PUR coating, as it is the case with comparable EPDM flooring from other manufacturers. Material does not become brittle when exposed to UV light and heat; it remains flexible.

Areas at Increased Risk of Staining

A transparent PUR coating can be applied to everroll® xtreme to give the floor a sealed, almost pore-free surface with a silk matt appearance. This makes cleaning noticeably easier and significantly increases its resistance to staining.

Outside and Wet Areas

The light-fastness of everroll® xtreme ensures that colours remain almost identical over extended periods of time. Its high resistance to weathering guarantees longevity. Under certain conditions, everroll® xtreme is also suitable for water play areas. In this case, we recommend the unsealed version. Please consult BSW before laying everroll® xtreme in exterior or wet areas.