

SPORT B

DESCRIPTION	Standard	
Maintenance Classification	-	Triple-Action Protocol®
Multilayer Surface	-	D-MAX™
Expanded Vinyl Backing	-	Vertical Closed Cell
Antibacterial	-	Sanosol®
Thickness	EN428	6.2 mm (± 0.244" / ± 1/4")
Wear Layer	-	2.1 mm (± 0.082")
Weight	EN430	4.4 kg/sq.m. (± 8 lbs/sq.y.)
Length	EN426	20.5 lm (± 67.25' Lft) or 24 lm (± 78.75' Lft)
Width	EN426	1.50 m (± 4' 11")

SPORT PROPERTIES

Force Reduction Ball Rebound	ASTM F2772-09	Level Classification 2
Energy Return	NF P 90 203	≥ 0.31 m/s
Vertical Deformation / Resiliency	EN 14809	≤ 3.5 mm
Uniform friction Coefficient of Friction	EN 13036-4	80 - 110

TECHNICAL CHARACTERISTICS

Static Load	-	≤ 0.5"
Abrasion Resistance	EN ISO 5470-1	≤ 350
Impact Resistance	EN 1517	≥ 8 N.m
Rolling Load Resistance	EN 1569	≥ 1500 N
	DIN 18032	≥ 1000 N
Chemical Resistance	-	Good
Light Reflection	CEN ISO 2813	≤ 30%

CLASSIFICATION

Fire Rating*	CAN/ULC S102.2-M88	Meets Canadian building code when tested in accordance
Environment	-	FloorScore™ Certified.
15 year limited warranty	-	Terms and conditions of the warranty are available on request.