

TECHNICAL INFORMATION



Physical properties

Total weight: 400 /m² (nominal)

Vinyl Weight: 310 /m² (nominal)



Substrate Type: Non Woven Fabric

Substrate weight: 90g/m² (nominal)

Other specifications available

Tensile Strength: MD 40 N/cm (nominal)

TD 30 N/cm (nominal)

Tear Strength: 4500 mN (nominal)



Roll size:

130cm x 30m - cut lengths available



Pattern Repeat

Reverse hang, straight match



Fire Rating:

Class 'O' to the requirements of Approved Document B of the British Building Regulations. Euroclass B - s2, d0.

Class A ASTM E-84 Tunnel Test.



Adhesive:

Fabric backed vinyls - Newmor Heavy.

Varies with substrate - please enquire.



Bacteria Resistance:

Contains an active Fungicide.



Light Fast:

Excellent Light Fastness

BS EN ISO 105-B02 6

LRV = Light reflective value

Specifications

Conforms to requirements of BS EN 15102, BS EN 259 and WAA - Quality Standard W-101.

Stain/Chemical Resistance:

Pass ASTM D-1308-1987 Federal Spot Test.

Resistant to temporary staining of oils, fats, mild acids and alkalis.

Quality Assurance:

Our management system and production procedures comply with ISO 9001: 2015, the internationally recognised Quality Standard.

Availability:

Every product stocked in depth.

5.00pm deadline for next day delivery.

(UK only)

Origin:

Designed, coloured, manufactured and stocked in the UK.

Warranty:

Newmor offers a five year warranty

against manufacturing defects.

Full details available on application.

Samples:

Larger samples are readily available on request.

Maintenance:

Fully washable and in most cases products can be scrubbed repeatedly to remove any marks without damaging the product itself.

Also able to withstand the use of chlorine releasing agent solutions.

Customise this design



youchoose™

Our Unique Re-Colouration Service

www.newmor.com



Newmor
WALLCOVERINGS

UK SALES:

T: 01938 551990

E: sales@newmor.com

EXPORT SALES:

T: + 44 (0) 1938 55 2671

E: enquires@newmor.com