

TECHNICAL INFORMATION



Physical properties

Total weight: 400 /m² (nominal)
Vinyl Weight: 310 /m² (nominal)



Substrate Type: Non Woven Fabric
Substrate weight: 90g/m² (nominal)

Other specifications available

Tensile Strength: MD 40 N/cm (nominal)
TD 30 N/cm (nominal)
Tear Strength: 4500 mN (nominal)



Roll size:

130cm x 30m - cut lengths available



Pattern Repeat Brushed Steel

Vertical: Free match
Horizontal: Free match

Manhattan

Vertical: Straight match
Horizontal: None



Fire Rating:

Class 'O' to the requirements of Approved Document B of the British Building Regulations (Class 1, BS 476 part 7).
Euroclass B - s2, d0. Class A ASTM E-84 Tunnel Test.



Adhesive:

Fabric backed vinyls - Newmor Heavy.
Varies with substrate - please enquire.



Bacteria Resistance:

Contains an active Fungicide.



Light Fast:

Excellent Light Fastness
BS EN ISO 105-B02 7/8

LRV = Light reflective value

Specifications

Conforms to requirements of BS EN 15102,
BS EN 259 and WAA - Quality Standard W-101.

Stain/Chemical Resistance:

Pass ASTM D-1308-1987 Federal Spot Test.
Resistant to temporary staining of oils,
fats, mild acids and alkalis.

Quality Assurance:

Our management systems and production
procedures comply with ISO 9001, the
internationally recognised Quality
Standard.

Availability:

Every product stocked in depth.
5.00pm deadline for next day delivery.
(UK only)

Origin:

Designed, coloured, manufactured and
stocked in the UK.

Warranty:

Newmor offers a five year warranty
against manufacturing defects.
Full details available on application.

Samples:

Larger samples are readily available on
request.

Maintenance:

Fully washable and in most cases products
can be scrubbed repeatedly to remove any
marks without damaging the product itself.
Most products are also able to withstand
the use of chlorine releasing agent solutions.



MADE IN GREAT BRITAIN
British Product | Global Support