

Product specification

Index: 1

PROFIGLAS

Installation steps



Product: P 6001

Description: Standard Glass textile wall covering for indoor walls and ceilings.



Composition Texturized yarn of glassfiber in warp.
Sliveryarn of glassfiber in weft.
Standard soft touch coating

Technical data:

Properties	Unit	Min value	Nom value	Max value
Width	mm	990	1000	1010
Length deviation	m	-0		
Thickness	mm		0.5	
Total weight	g / m ²	80	95	110
Tensile strength				
Warp direction	N / 5cm	161	190	
Weft direction	N / 5cm	145	170	

Glue consumption Approx. 250 g / m². See also instructions on the glue bucket.

Paint consumption First coating Second coating
m² / litre 4.6 9.4


Facing side	Reverse side marking	Pattern matching
Facing side is the INSIDE of the roll.	No marking on this product	Straight match - thread to thread
 		
		Pick over warpthread against pick under

Allowed amount of marked spot faults

Roll length 15m	Max 2
Roll length 25 & 30m	Max 3
Roll length 50m	Max 4

Note: A joint can occur in a roll and is considered as a spot fault.

Certificates:



Storage: -10 to +50 degrees Celcius
Shelf life: within 2 years after production

Information above is accurate to the best of our knowledge. Our products are subject to rigorous quality control along the production

process to ensure conformance. Divergence within our tolerance may occur.